


# I-242 PARTS LIST

# HELIOS PRO 90



Part #	Description	Cost	Qty	Total	Part #	Description	Cost	Qty	Total
871N	Female Axle	\$0.40			3243	Strap - Black	\$1.50		
862	Male Axle Screw	\$0.40			3343	Clip - Silver/Red	\$1.00		
996	Bearing Alignment Insert	\$0.40			2242	Liner - Specify sz 7-12	\$10.00		
775	Bearing Spacer	\$0.20			BF9024WS	Wheel - 90mm Racing	\$6.00		
608B9	Bearing - ABEC 9	\$2.50			979	Heel Stop Insert	\$0.40		
998	Male Heel Stop Screw	\$0.40			756B	Heel Stop - Black	\$1.50		
749	Female Axle (Brake)	\$0.40			755	Heel Stop Bracket	\$1.50		

All orders must be paid by check, Visa, or Mastercard prior to shipment  
 All orders are required to be faxed or mailed with signature

CA residents add 8% tax  
 IL residents add 7.25% tax  
 PA residents add 6% tax

Subtotal	
Tax	
Shipping and Handling	\$6.25
<b>TOTAL</b>	

Name: \_\_\_\_\_ Signature: \_\_\_\_\_ Phone: \_\_\_\_\_

Address: \_\_\_\_\_ City: \_\_\_\_\_ State: \_\_\_\_\_ Zip: \_\_\_\_\_

MC or Visa #: \_\_\_\_\_ Exp Date: \_\_\_\_\_

1. Check the axle screws on each wheel. The male and female should be tightened firmly prior to each use.
2. Check heel stop screw before skating. The male and female should be tightened firmly. If heel stop shows substantial wear, it should be replaced.

1. Prüfen sie die schrauben aller rollen, schraube und mutter vor gebrauch gut festdrehen.
2. Prüfen sie die schraube beim stopper bevor sie fahren. Schraube und mutter gut befestigen. Ersetzen sie den stopper, wenn er abgenutzt ist.

1. Sur chaque roue, vérifiez les vis de l'essieu. Les vis males et femelles doivent être serrées fermement avant l'utilisation des patins.
2. Vérifiez les vis du frein avant l'utilisation des patins. Les vis males et femelles doivent être serrées fermement. Si le frein arriere montre des signes apparents d'usure. Veuillez le remplacer.

1. Cheque los tornillos de cada rueda, macho y hembra de los tornillos deberan apretarse antes de cada uso.
2. Cheque todos los tornillos del freno para asegurarse que esten bien apretados. Si nota que la goma del freno esta gastada, esta debera ser reemplazada por una nueva